

TWSD11 c/w 1 1/2" Square Drive

| Pressure In | TORQUE | | Pressure In |
|-------------|--------|--------|-------------|
| | PSI | FT.LBS | |
| 1200 | 1313 | 1779 | 83 |
| 1400 | 1532 | 2075 | 97 |
| 1600 | 1750 | 2372 | 110 |
| 1800 | 1969 | 2668 | 124 |
| 2000 | 2188 | 2965 | 138 |
| 2200 | 2407 | 3261 | 152 |
| 2400 | 2626 | 3558 | 165 |
| 2600 | 2844 | 3854 | 179 |
| 2800 | 3063 | 4151 | 193 |
| 3000 | 3282 | 4447 | 207 |
| 3200 | 3501 | 4744 | 220 |
| 3400 | 3720 | 5040 | 234 |
| 3600 | 3938 | 5337 | 248 |
| 3800 | 4157 | 5633 | 262 |
| 4000 | 4376 | 5930 | 276 |
| 4200 | 4595 | 6226 | 290 |
| 4400 | 4814 | 6522 | 303 |
| 4600 | 5032 | 6819 | 317 |
| 4800 | 5251 | 7115 | 331 |
| 5000 | 5470 | 7412 | 345 |
| 5200 | 5689 | 7708 | 358 |
| 5400 | 5908 | 8005 | 372 |
| 5600 | 6126 | 8301 | 386 |
| 5800 | 6345 | 8598 | 400 |
| 6000 | 6564 | 8894 | 414 |
| 6200 | 6783 | 9191 | 427 |
| 6400 | 7002 | 9487 | 441 |
| 6600 | 7220 | 9784 | 455 |
| 6800 | 7439 | 10080 | 468 |
| 7000 | 7658 | 10377 | 482 |
| 7200 | 7877 | 10673 | 496 |
| 7400 | 8096 | 10970 | 510 |
| 7600 | 8314 | 11266 | 524 |
| 7800 | 8533 | 11563 | 538 |
| 8000 | 8752 | 11859 | 552 |
| 8200 | 8971 | 12156 | 565 |
| 8400 | 9190 | 12452 | 579 |
| 8600 | 9408 | 12749 | 593 |
| 8800 | 9627 | 13045 | 607 |
| 9000 | 9846 | 13341 | 620 |
| 9200 | 10065 | 13638 | 634 |
| 9400 | 10284 | 13934 | 648 |
| 9600 | 10502 | 14231 | 662 |
| 9800 | 10721 | 14527 | 676 |
| 10000 | 10940 | 14824 | 690 |



Top 20% capacity for break-out purposes only. Do not use for regular tightening.

Use a larger tool.

Unit 12, Blackfriars Court, Excalibur Road, Beacon Business Park, Great Yarmouth, Norfolk NR31 7RQ

Tel: 01493 603797

e-mail: sales@gee-force.co.uk www.gee-force.co.uk